NEW "QUICK TURN" ALL GLASS ENTRANCE DOORS

DELIVERY TIME FROM 3-DAYS



EXCELLENT LEAD TIMES TO MEET YOUR MOST DEMANDING PROJECT SCHEDULES

3 DAYS + SHIPPING FOR STOCK RAIL/RAIL STYLE DOOR HARDWARE & GLASS WITH STANDARD SIDELITES:

- FULL LENGTH RAILS TOP & BOTTOM
- DOOR SIZE: 35-3/4" X SPECIFIED HEIGHT UP TO 108"

4 DAYS + SHIPPING FOR ANY PATCH/RAIL/LOCK/HANDLE COMBINATION HARDWARE & GLASS WITH STANDARD SIDELITES:

- FULL LENGTH RAILS TOP & BOTTOM WITH ALTERNATE STOCK HANDLES
- ANY PATCH, LOCK, RAIL, AND STOCK HANDLE COMBINATION
- DOOR SIZE: 35-3/4" X SPECIFIED HEIGHT UP TO 102" PATCH & 108" FULL RAILS





5 DAYS + SHIPPING FOR STOCK HARDWARE & CUSTOM GLASS (SIDELITES & TRANSOM) RO 119" MAX. - PATCH ONLY

- FULL LENGTH RAILS TOP & BOTTOM WITH ALTERNATE STOCK HANDLES
- ANY PATCH, LOCK, RAIL, AND STOCK HANDLE COMBINATION
- DOOR SIZE: 35-3/4" X SPECIFIED HEIGHT UP TO 102" PATCH & 108" FULL RAILS

AVAILABLE IN MATTE BLACK OR BRUSHED STAINLESS STEEL
SIDELITE QUANTITIES GREATER THAN 10 MAY REQUIRE ADDITIONAL LEADTIME
ORDER CUTOFF TIME IS 1PM PST/PDT
SEE BACKSIDE FOR ADDITIONAL INFORMATION AND ORDER FORM



Phone: 1 (800) 552-2227



All Glass Entrance Quick-Turn Order Form

Date: PO	PO#:	Company Name:
Contact Name:	Phone:	Email Address:
Project Name:		

Additional Information on Each Configuration

Stock Rail/Rail Style Door:

- Stock Handle Fab for 12" D-Pull or 24" Ladder Pull
- 42" Center Handle Height for Handle Holes; 4" Hole Centerline in from Glass Edge

Patch/Rail/Lock/Handle Combination:

- Alternate Stock Handle Fab; Custom Hole Placement
- Patch Hardware Cut-Outs

Stock Hardware & Custom Glass:

- Alternate Stock Handle Fab; Custom Hole Placement
- Patch Hardware Cutouts
- Floating Headers, Patch Fittings for Transoms & Sidelites
- Wall Mount Barn Door Style Doors

Glass Thickness: 1/2"	Aluminum Header:	Locks:
Glass Type: Clear	ass Type: Clear □Yes □No	
Standard Door Opening Width: 36" □ Continuous w/Glazing po		☐Keyed Cylinder/Thumb Turn
Net Opening Height:	□ Matte Black (1 3/4" x 4 1/2")	
Select Door Type:	☐ Brushed Stainless Steel (1 7/8"	Dust Proof Strikes:
□P/P □R/R □P/R □R/P	x 4 11/16") □ Floating Header	□Yes □No
		Quantity
	Closer: 'Yes 'No Floor Closer Overhead Concealed	Sidelite Rail & Accessories: Continuous Header w/Glazing Pocket 15/8" x 1 5/8" U-Channel
Door Opening Height:	□Hold Open □ 90° □ 105°	□1 5/8" x 3/4" U-Channel
(Max. per NGA/GANA)	□No Hold Open □ 90° □ 105°	Wet Glaze:
		□1" □1.5" □2"
Finish:	Door Pull:	
□Brushed Stainless Steel	□Yes □No	Note:
□Matte Black	□12" Back to Back D-Pull	Maximum Net Opening Height
	□24" Ladder Pull	is 119"
Тор:	□Other	 Minimum Sidelite Width is 12" w/Transom & 6" Flat Polish Only
□Patch Fitting	(For "Other", Hartung will Con-	
□Transom Patch □Wall Mount □Glass Mount	firm Availability & Lead-Time)	• Standard Sidelite Gap is 1/8"
□Full Length Door Rail (square style, 4")	Color:	Other Sidelite Gap
	□Brushed Stainless Steel	
Bottom:	□Matte Black	Clidous
□Patch Fitting □Hydraulic Patch □Full		Sliders:
Length Door Rail (square style, 4")	Standard Handle Location:	□Laguna □Carmel Color:
	• 42" Center Line from Bottom of	□Brushed Stainless Steel
	Door	□Matte Black
	4" Center Line from Edge of Door	LIVIALLE DIALK

Revision: November 2024 Thank you for your business!

^{**}For other than doors only, please provide diagrams with dimensions & layout ** **